

CONTACTS

info@sprintech.eu www.sprintech.eu

Mobile: +39 338 14 55 199 Fax: +41 (0) 27 455 90 60

## MAIL ADDRESS

CD Project

P.O.Box 224 - 3960 Sierre

Switzerland

Handlebar type Bike model suitability Surface of the mirror Type of mirror Weight, clamping system included Fixing side(s) Single mirror Diameter of the bar How to fix it Mirror(s) packaging

Quantity: single unit packaging per carton

Quantity: pair packaging per carton

Colours

**RACING** 



**RACING XL** 

CITY



**CITY XL** 



COMPACT

drop down racing bike 24 cm<sup>2</sup> ABS, convex and chrome coated 0,33 grs

left and/or right different for left or right side

20 mm

1. remove the original cap

2. insert the Sprintech® cap without removing the tape

3. insert the mirror and adjust it

available in packaging of one unit (left or right) or in pair.

60

black, white, red, blue, yellow, green

drop down racing bike 29 cm<sup>2</sup>

safety glass 0,43 grs

left or right

same for left and right side

20 mm

1. remove the original cap

2. insert the Sprintech® cap without removing the tape

3. insert the mirror and adjust it

available in packaging of one unit (suitable for both left or right side) 60

not available black

straight

MTB. city bike. e-bike and scooter 24 cm<sup>2</sup>

ABS, convex and chrome coated

0,65 grs

left and/or right

different for left or right side

from 16 to 20 mm

1. remove the original cap

2. assemble the clamping system parts

3. insert the mirror

4. adjust the mirror and screw

to secure it

available in packaging of one unit (left or right) or in pair.

50 25

black

straight

MTB, city bike, e-bike and scooter

29 cm<sup>2</sup>

safety glass

0,75 grs

left and/or right

same for left and right side

from 16 to 20 mm

1. remove the original cap

2. assemble the clamping system parts

3. insert clamping system and mirror

4. adjust the mirror and screw

to secure it

one unit per packaging, assembled and ready to be inserted and screwed

not available

black

straight

MTB. city bike. e-bike and scooter

38,5 cm<sup>2</sup>

safety glass

0,99 grs

left or right

same for left and right side

from 16 to 20 mm

1. remove the original cap

2. insert the clamping system

2. insert the mirror

3. adjust the mirror and screw

to secure it

one unit per packaging, assembled and

ready to be inserted and screwed

not available

black