

CONTACTS

info@sprintech.eu www.sprintech.eu

Mobile: +39 338 14 55 199 Fax: +41 (0) 27 455 90 60

MAIL ADDRESS

CD Project

P.O.Box 224 - 3960 Sierre

Switzerland

Handlebar type
Bike model suitability
Surface of the mirror
Type of mirror
Weight, clamping system included
Fixing side(s)
Single mirror
Diameter of the bar
How to fix it

Mirror(s) packaging

Quantity: single unit packaging per carton

Quantity: pair packaging per carton

Colours

RACING



drop down
racing bike
24 cm²
ABS, convex and chrome coated
33 grs
left and/or right
different for left or right side
20 mm
1. remove the original cap

remove the original cap
 insert the Sprintech® cap without removing the tape
 insert the mirror and adjust it

available in packaging of one unit (left or right) or in pair.

60 45

black, white, red, blue, yellow, green

RACING XL



drop down
racing bike
29 cm²
safety glass
42 grs
left or right
same for left and right side
20 mm
1. remove the original cap
2. insert the Sprintech® cap without

removing the tape
3. insert the mirror and adjust it
available in packaging of one unit
(suitable for both left or right side)
60

not available

black

straight

CITY

MTB, city bike, e-bike and scooter 24 cm²

ABS, convex and chrome coated 75 grs

left and/or right different for left or right side

1. remove the original cap

2. assemble the clamping system parts

3. insert the mirror

from 16 to 20 mm

4. adjust the mirror and screw to secure it

available in packaging of one unit (left or right) or in pair.

50 25

25 black CITY XL



straight
MTB, city bike, e-bike and scooter
29 cm²
safety glass
84 grs

left and/or right same for left and right side

1. remove the original cap

from 16 to 20 mm

2. assemble the clamping system parts

3. insert clamping system and mirror

4. adjust the mirror and screw

to secure it one unit per packaging, assembled and ready to be inserted and screwed

45

not available black

straight MTB, city bike, e-bike and scooter 38,5 cm²

COMPACT

safety glass

105 grs

left or right

same for left and right side

from 16 to 20 mm

1. remove the original cap

2. insert the clamping system

2. insert the mirror

3. adjust the mirror and screw

to secure it

one unit per packaging, assembled and ready to be inserted and screwed

45

not available

black